

### **Amendments to the Claims:-**

This listing of claims will replace all prior versions, and listings, of claims in the application:-

### **Listing of Claims:-**

1. (Original) A paint roller for applying paint onto a surface comprising:  
a frustoconically-shaped applicator having:  
a coupler end;  
a distal end;  
an external surface between the coupler end and the distal end; and  
a paint-absorbable member;  
a circular integral guard disposed at the coupler end; and  
a rolling guide disposed at the distal end  
wherein the rolling guide coacts with a resilient means to permit rotation about  
an axis of rotation.
2. (Original) The paint roller of claim 1, wherein the planar cross-section of the  
coupler end is not the same as the planar cross-section of the distal end.
3. (Original) The paint roller of claim 1, wherein the frustoconically-shaped  
applicator further comprising a chamber defined by the coupler end, the distal end  
and the external surface joining the coupler and distal ends; the chamber further  
having a plurality of perforations.
4. (Original) The paint roller of claim 3, wherein the chamber is accessible by a  
closable inlet.
5. (Original) The paint roller of claim 1, wherein the coupler end has a coupler to fit  
a handle.
6. (Original) The paint roller of claim 1, wherein the coupler end permits rotation of  
the paint applicator about an axis.
7. (Original) The paint roller of claim 1, wherein the diameter of the integral guard is  
predetermined to allow the circular integral guard to contact the surface only when  
excessive force is used to apply paint.
8. (Previously presented) The paint roller of claim 1, wherein the resilient means is  
radially-disposed about the axis of rotation of the frustoconically-shaped  
applicator.
9. (Previously presented) The paint roller of claim 1, wherein the resilient means is  
held in place by a retainer.
10. (Previously presented) The paint roller of claim 1, wherein the rolling guide  
permits eccentric rotation of the paint applicator in use.
11. (Withdrawn-currently amended) A method of selectively applying paint onto

surfaces and surface corners, the method comprising:

using a paint roller comprising a frustoconically-shaped applicator having a coupler end, a distal end an external surface between the coupler end and the distal end, and a paint-absorbable member; an [[and]] circular integral guard disposed at the coupler end and a rolling guide disposed at the distal end wherein the rolling guide coacts with a resilient means to permit rotation about an axis of rotation;

whereby the integral guard prevents a paint-absorbable surface mounted on the applicator from being excessively compressed, thereby preventing an undesirably thick coat of paint from being applied, and the rolling guide permits paint to be precisely applied to surface corners and uneven surfaces.

12. (Previously presented) The paint roller of claim 1, wherein the planar cross-section of the coupler end is the same as the planar cross-section of the distal end.